



CA32-U Series 32A AC Charger

Model		CA32-U1	CA32-U2	CA32-UA	CA32-UE
Power					
Input	Voltage	200~240 VAC, Single phase (L1+N+Gnd)			
	Frequency	50/60Hz			
Output	Voltage	200-240 VAC			
	Max. current	Max 32A			
	Power	7kW			
Interface					
Connection standard		SAE J1772 (Type 1)			IEC62196-2 Type2
Button		Emergency on/off			
LED		Booting (purple on), Ready (blue on), Charging (green blinking), Finish (green on) Warning, Error (red blinking), Out of service (yellow on)			
Voice prompt		Yes			
HMI		None	5" color touch screen		
Electric Meter		IC meter	Standard alone MID		
Communication					
RS-485		One			
Ethernet		10/100 Mbps Ethernet (OCPP 1.6J)			
reader		ISO 14443-A, MIFARE		Multi paymet terminal	ISO 14443-A, MIFARE
Wi-Fi		Optional	Optional		
4G		None	Optional		
Protection					
Protection rating		IP55 / IK9			
Safety		Surge protection, High/low voltage, Over temperature, Overcurrent, Insulation detection Ground detection			
Certification		CNS15511 / VPC			
Environment					
Temperature		-30~50℃	-20~50℃		
Humidity		5%~95%			
Others					
Dimension		Body: L 440 x W 320 x H 165mm			
Cable length		5M			
Installation		Wall mount / Pile (optional)			

TONGYA TELECOMMUNUCATUOIN INDUSTRY Co., LTD.
 753, Chung Cheng Rd., Shulin Dist., New Taipei
 TEL: +886-2-26893781
www.tongya.com.tw