## **Ticket Vending Machine**



The ticket machine CX-850-4 is installed in security public areas. This ticket machine is bundled with a bill acceptor and thermal printer into the sam unit. It has built-in a real time clock for ticketing stamping, providing an easy and quick way to insert bill to get a ticket/receipt at user convenience.

By being **RMS** (**R**emote **M**anagement **S**ystem) accessed, all daily report, collection report and alarm report information are easy attainable at any time. The ticket machine with telemetry system allows the owner to run their business more efficiently through any PC over IP network. It is suitable for food court, quick hair cut shop and other outlets where printing a receipt is requested.



## CX-850-4

## **Main Features**

- Easy to use and user-friendly operation
- LCD display with backlight
- Bill acceptor accepts bank notes
- Anti-jam/ Anti-drag technology
- Thermal printer in getting ticket
- Full/partial cut function
- Trouble diagnostics
- Cash box full and removed detected
- Auto short SMS to report to mobile phone
- On site keypad programmable
- Remote management capabilities -option
- Wall mount -option

| Technical Specifications |                                     |                                    |
|--------------------------|-------------------------------------|------------------------------------|
| Power                    |                                     | AC110-240V, 50/60Hz                |
| Metal Cabinet            |                                     | 1.6mm steel over powder coating    |
| LCD Display              |                                     | 16 digits x 4 lines with backlight |
| Bill Acceptor            |                                     |                                    |
| Bill Capacity            |                                     | 500pcs                             |
| Transmission time        |                                     | App. 3sec. to stack                |
| Thermal printer          |                                     |                                    |
| Thermal Printer          | Paper width: 56mm±0.5mm             |                                    |
| Printing Speed           | 40mm/sec                            |                                    |
| Resolution               | 8 dots/mm                           |                                    |
| GPRS modem               |                                     |                                    |
| Air Interface            | GSM freq.: 850-1900MHz, 900-1800MHz |                                    |
| SIM Card Holder          | 3V SIM Card                         |                                    |
| Dimensions & Weight      |                                     |                                    |
| Dimensions               | 224mm(W) x 209mm(D) x 530mm(H)      |                                    |
| Weight                   | 18kgs                               |                                    |
| Environment              |                                     |                                    |
| Temperature              | -5°C ∽ +60°C                        |                                    |
| Humidity                 | 0% to 90% Non-Condensing            |                                    |